



# EMSL Analytical, Inc.

1056 Stelton Road Piscataway, NJ 08854

Tel/Fax: (732) 981-0550 / (732) 981-0551

<http://www.EMSL.com> / [piscatawaylab@emsl.com](mailto:piscatawaylab@emsl.com)

EMSL Order: 052000080

Customer ID: TMAS50

Customer PO:

Project ID:

**Attention:** Kevin Burns  
T & M Associates  
1455 Broad St  
Suite 250  
Bloomfield, NJ 07003

**Phone:** (908) 347-4396

**Fax:** (732) 671-7365

**Received Date:** 01/07/2020 02:21 PM

**Analysis Date:** 01/07/2020

**Collected Date:** 01/07/2020

**Project:** BB0E-00187 / Bayonne BOE, Nicholas Oresko School

## Test Report: Fiber Count by Phase Contrast Microscopy (PCM), NIOSH 7400 Method - A Rules, Revision 3, Issue 3, 6/15/2019

Sample	Location	Sample Date	Volume (L)	Fibers	Fields	LOD (fib/cc)	Fibers/mm <sup>2</sup>	Fibers/cc	Notes
01072001	Exterior Near School Entrance Sign	01/07/2020	1238	<5.5	100	0.002	<7.01	<0.002	
<i>052000080-0001</i>									
01072002	Exterior Area Near Church Site	01/07/2020	1238	<5.5	100	0.002	<7.01	<0.002	
<i>052000080-0002</i>									
01072003	Main Roof; Exterior At HVAC Unit Church Site	01/07/2020	1237	<5.5	100	0.002	<7.01	<0.002	
<i>052000080-0003</i>									
01072004	Field Blank	01/07/2020		<5.5	100		<7.01		Field Blank
<i>052000080-0004</i>									
01072005	Field Blank	01/07/2020		<5.5	100		<7.01		Field Blank
<i>052000080-0005</i>									

The results reported have been blank corrected as applicable.

Analyst(s):  
Kurt Carlson PCM 5

Chaiyut Sae Lao, Laboratory Manager  
or other Approved Signatory

Limit of detection is 7 fibers/mm<sup>2</sup>. Fiber counts outside the recommended fiber density range of the method (100-1300 f/mm<sup>2</sup>) have greater than optimal variability and are probably biased. EMSL maintains liability limited to cost of analysis. This report relates only to the samples reported above and may not be reproduced, except in full, without written approval by EMSL. EMSL bears no responsibility for data reported that relies on information provided by the client, sample collection activities, or analytical method limitations. Interpretation and use of test results are the responsibility of the client. Results have been blank corrected as applicable. The report reflects the samples as received. Measurement of uncertainty available upon request. The results in this report meet all requirements of the NELAC standards unless otherwise noted. Intra-laboratory Sr values: 5-20 fibers = 0.34, 21-50 fibers = 0.24, 51-100 fibers = 0.22. Inter-laboratory Sr values (Average of EMSL round robin data) = 0.34. Samples analyzed by EMSL Analytical, Inc. Piscataway, NJ NYS ELAP 11423, NJ NELAC 12037, CT PH-0266

Initial report from: 01/08/2020 08:06 AM